



QTY.	PIPE SIZE NPS	A (IN)	PRESSURE* (PSI)	NOTES
	2"	12"	516	
	2-1/2"	14"	387	
	3"	14"	316	
	4"	16"	232	
	5"	17"	191	
	6"	18"	165	
	8"	20"	234	
	10"	24"	230	
	12"	25"	161	

\* FOR SAFE WORKING PRESSURE ABOVE 70°F, MULTIPLY PRESSURE SHOWN AT 70°F TIMES CORRECTION FACTOR OF REQUIRED TEMP.

TEMP °F	FACTOR
70	1.0
150	.97
200	.94
250	.92
300	.88
350	.86
400	.83
450	.81
500	.78
600	.77

MAX INTERMITTENT OFFSET FROM ⊕  1/8"  
 MAX PERMANENT OFFSET FROM ⊕  3/8"

CUSTOMER: \_\_\_\_\_

PROJECT: \_\_\_\_\_

ENGINEER: \_\_\_\_\_

PURCHASE ORDER \_\_\_\_\_



REV.	DATE	
	5331 Quam Ave., N.E. St. Michael, MN 55376 TEL: 763-201-2151 FAX: 763-201-2134 www.engineeredflex.com	
<b>ENGINEERED FLEXIBLE PRODUCTS, INC.</b>		
STAINLESS STEEL BRAIDED CONNECTOR		
DRAWN BY:	AD	DATE: 10/12/2010
APPROVED:		DATE:
SCALE:	DRAWING NUMBER:	
NONE		