



QTY.	A PIPE SIZE	B PIPE SIZE	C FACE TO FACE	PRESSURE* (PSI)	NOTES
	2-1/2"	2"	13"	387	
	3"	2"	13"	316	
	4"	2"	13"	232	
	3"	2-1/2"	13"	316	
	4"	2-1/2"	13"	232	
	5"	2-1/2"	16"	191	
	4"	3"	13"	232	
	5"	3"	16"	191	
	6"	3"	17"	165	
	5"	4"	16"	191	
	6"	4"	17"	165	
	8"	4"	18"	235	
	6"	5"	17"	165	
	8"	5"	18"	235	
	8"	6"	18"	235	
	10"	6"	18"	230	
	10"	8"	18"	230	
	12"	10"	20"	160	

* FOR SAFE WORKING PRESSURE ABOVE 70°F, MULTIPLY PRESSURE SHOWN AT 70°F TIMES CORRECTION FACTOR OF REQUIRED TEMP.

TEMP °F	FACTOR
70	1.0
150	.97
200	.94
250	.92
300	.88
350	.86
400	.83
450	.81
500	.78
600	.77

CUSTOMER: _____

PROJECT: _____

ENGINEER: _____

PURCHASE ORDER: _____



REV.	DATE
5331 Quam Ave., N.E. St. Michael, MN 55376 TEL: 763-201-2151 FAX: 763-201-2134 www.engineeredflex.com	
MODEL CRPCS FLANGED REDUCING CONNECTOR	
DRAWN BY:	DATE: 8/03/2011
APPROVED:	DATE:
SCALE: NONE	DRAWING NUMBER: CRPCS